

	MAXXUM 110 MULTICONTROLLER	MAXXUM 120 MULTICONTROLLER	MAXXUM 130 MULTICONTROLLER	MAXXUM 115 MULTICONTROLLER	MAXXUM 125 MULTICONTROLLER	MAXXUM 140 MULTICONTROLLER
MOTOR						
Aspiratie / Managementul consumului de combustibil						
Numar cilindrii / capacitate (cm3)	4/4485	4/4485	4/4485	6/6728	6/6728	6/6728
Putere nominala ECE R120 (kW/cp(CV))	82/112	90/122	97/132	86/117	93/127	104/141
Putere nominala ECE R120 ¹⁾ - managementul puterii (kW/cp(CV))	97 / 132	104 / 141	104 / 141	104 / 141	112 / 152	123 / 167
Putere maxima cu Managementul Puterii Motorului (kW/cp(CV))	105 / 142	107 / 145	107 / 145	112 / 152	120 / 163	131 / 178
Cuplu maxim la viteza motorului (Nm/rpm)	520 / 1400	563 /1400	594 / 1400	543 / 1400	593 / 1400	613 / 1400
TRANSMISIE						
Tip	Transmisie semi-automata, PowerShuttle					
Numar viteze / cu senile (FxR)	16x16 / 32x32	16x16 / 32x32	16x16 / 32x32	16x16 / 32x32	16x16 / 32x32	16x16 / 32x32
Number viteze 40 kph / 50 kph (FxR)	17x16 / 17x16	17x16 / 17x16	17x16 / 17x16	17x16 / 17x16	17x16 / 17x16	17x16 / 17x16
TRACTIUNE INTEGRALA SI VIRAJ						
Tip	Auto 4WD si Auto Difflock					
Raza minima de rotatie (m)	4.04	4.04	4.04	4.36	4.36	4.36
SISTEM HIDRAULIC						
Control	Standard: EHC (control electronic al cuplajului) cu control al deplasarii carligului					
Capacitate maxima de ridicare (kg)	7864	7864	7864	7864	7864	7864
GREUTATE						
Greutate minima (kg)	4820	4820	4820	4490	4490	4490
Greutate totala admisa fara balast (kg)	9000	9000	9000	9000	9000	9000

¹⁾ ECE R120 corespunde ISOTR 14396